



**Construction Products Regulation (EU) 305 2011  
Declaration of Performance (DoP)  
No: DOP2015-1-HS20-CLEAR**

1. **Unique identification code of the product - type:**  
**HS20 CLEAR**
2. **Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):**  
For batch number; see product packaging.
3. **Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacturer:**
4.  
EN15651-1: F-INT: Sealant for façade for interior application.
5. **Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):**  
Hodgson Sealants (Holdings) Ltd.  
Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.
6. **Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12 (2):**
7.  
Not applicable.
8. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**  
System 4  
System 3 for reaction to fire
9. **In case of declaration of performance concerning a construction product covered by a harmonised standard:**  
**EN15651-F-INT**  
The notified body SKZ – TeCona GmbH, identification number 1213 performed testing for reaction to fire and issued a test report.
10. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**  
Not Applicable.



**11. Declared Performance**

<b>EN 15651-1: F-INT</b> <b>Pre-Conditioning: Method B.</b> <b>Substrate: Glass – without primer.</b>		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	Class E	
Release of Chemicals	See product safety data sheet	
Water Tightness & Air Tightness as determined by:		
Resistance to flow	≤ 3mm	EN 15651-1: 2012
Loss of volume	≤ 45%	EN 15651-1: 2012
Tensile properties: elongation at break	≥ 25%	EN 15651-1: 2012
Durability	Pass	EN 15651-1: 2012

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant


**12. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for on behalf of Hodgson Sealants (Holdings) Ltd. by



Craig Wear  
Technical Services Consultant  
Beverley, 13<sup>th</sup> April 2015



 1213
Hodgson Sealants (Holdings) Ltd, Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.  15  Reference No: DOP2015-1-HS20-CLEAR
<b><u>HS20-CLEAR</u></b> EN 15651-1: F-INT Pre-Conditioning: Method B. Substrate: Glass – without primer.
EN 15651-1: F-INT: Sealant for façade for interior application. Reaction to Fire Class F Resistance to flow $\leq 3\text{mm}$ Loss of volume $\leq 45\%$ Tensile properties: elongation at break $\geq 25\%$ Durability Pass