



**Construction Products Regulation (EU) 305 2011  
Declaration of Performance (DoP)  
No: DOP2017-1-HYGIENESEAL**

1. **Unique identification code of the product - type:**

**HYGIENESEAL**

2. **Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):**

For batch number; see product packaging.

3. **Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacturer:**

4.

EN15651-1: F-INT: Sealant for façade for interior application.  
EN15651-3: S: Sealants for sanitary joints.

5. **Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):**

Hodgson Sealants (Holdings) Ltd.  
Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.

6. **Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12 (2):**

Not applicable.

7. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

System 3

8. **In case of declaration of performance concerning a construction product covered by a harmonised standard:**

**EN15651-F-INT  
EN15651-S**

The notified body 4Ward Testing Ltd, identification number 2538 performed initial type tests under system 3 and issued report.

9. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

Not Applicable.



**10. Declared Performance**

<b>EN 15651-1: F-INT</b>		
<b>Pre-Conditioning: Method A.</b>		
<b>Substrate: Mortar – without primer.</b>		
<b>Essential Characteristic</b>	<b>Declared Performance</b>	<b>Harmonised Standard</b>
Reaction to Fire (EN13501)	NPD	
Release of Chemicals	See product safety data sheet	
Resistance to flow (ISO7390)	≤ 3mm	EN 15651-1: 2012
Loss of volume (ISO10563)	≤ 10%	EN 15651-1: 2012
Elongation at break (ISO8339)	≥ 25%	EN 15651-1: 2012
<b>EN 15651-3: S</b>		
<b>Essential Characteristic</b>	<b>Declared Performance</b>	<b>Harmonised Standard</b>
Reaction to Fire (EN13501)	NPD	
Release of Chemicals	See product safety data sheet	
Resistance to flow (ISO7390)	≤ 3mm	EN 15651-3: 2012
Loss of volume (ISO10563)	≤ 10%	EN 15651-3: 2012
Elongation at break (ISO10591)	NPD	EN 15651-3: 2012
Microorganisms: intensity of growth	2	EN 15651-3: 2012

**Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:**

Not relevant


**11. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for on behalf of Hodgson Sealants (Holdings) Ltd. by



Craig Wear  
Technical Services Consultant  
Beverley, 10<sup>th</sup> December 2017



 <b>2538</b>
<b>Hodgson Sealants (Holdings) Ltd, Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.</b>
<b>17</b>
<b>Reference No: DOP2017-1-HYGIENESEAL</b>
<b><u>HYGIENESEAL</u></b> <b>EN 15651-1: F-INT</b> <b>EN 15651-3: S2</b> <b>Pre-Conditioning: Method A.</b> <b>Substrate: Mortar – without primer.</b>
<b>EN 15651-1: F-INT-EXT: Sealant for façade for interior application.</b> <b>EN15651-3: S: Sealants for sanitary joints.</b> Reaction to Fire NPD Resistance to flow ≤3mm Loss of volume ≤10% Elongation at break >25% Tensile properties at maintained extension after immersion in water NPD Microorganisms intensity of growth 2