



Construction Products Regulation (EU) 305 2011
Declaration of Performance (DoP)
No: DOP2014-1-Aquacaulk

1. **Unique identification code of the product - type:**
Aquacaulk
2. **Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):**
For batch number; see product packaging.
3. **Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacturer:**
EN15651-1: F-EXT-INT: Sealant for façade for interior and exterior application.
4. **Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):**
Hodgson Sealants (Holdings) Ltd.
Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12 (2):**
Not applicable.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
System 3
7. **In case of declaration of performance concerning a construction product covered by a harmonised standard:**
EN15651-F-INT-EXT
The notified body 4ward Testing Ltd, identification number 2538 performed initial type tests under system 3 and issued report no NLR1796.
8. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**
Not Applicable.



9. Declared Performance

EN 15651-F-INT-EXT: CLASS – 12.5P Pre-Conditioning: Method A. Substrate: Mortar without primer.		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	Class F	
Release of Chemicals	See product Safety Data Sheet	
Water Tightness & Air Tightness as determined by:		
Resistance to flow (ISO7390)	≤ 3mm	EN 15651-1: 2012
Loss of volume (ISO10563)	≤ 25%	EN 15651-1: 2012
Adhesion and cohesion properties after immersion in water (ISO10591)	≥ 25%	EN 15651-1: 2012
Adhesion and cohesion properties at constant temperature (ISO9046)	NF	EN 15651-1: 2012

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:
Not relevant


10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of Hodgson Sealants (Holdings) Ltd. by



Craig Wear
Technical Services Consultant
Beverley, 13th June 2014



 2538
Hodgson Sealants (Holdings) Ltd, Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK. 14 Reference No: DOP2014-1-Aquacaulk
<u>Aquacaulk</u> EN 15651-1-F-INT-EXT: CLASS 12.5P Pre-Conditioning: Method A. Substrate: Mortar without primer
EN15651-1-F-INT-EXT: Sealant for façade for interior and exterior application. Reaction to fire Class F Resistance to flow $\leq 3\text{mm}$ Loss of volume $\leq 25\%$ Adhesion and cohesion properties after immersion in water $\geq 25\%$ Adhesion and cohesion properties at constant temperature NF