



**Construction Products Regulation (EU) 305 2011  
Declaration of Performance (DoP)  
No: DOP2015-1-HS30**

1. **Unique identification code of the product - type:**  
**HS30**
  
2. **Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):**  
For batch number; see product packaging.
  
3. **Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacturer:**
4.  
EN15651-1: F-EXT-INT: Sealant for façade for interior and exterior application.
  
5. **Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):**  
Hodgson Sealants (Holdings) Ltd.  
Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.
  
6. **Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12 (2):**
7.  
Not applicable.
  
8. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**  
System 3
  
9. **In case of declaration of performance concerning a construction product covered by a harmonised standard:**  
**EN15651-F-INT-EXT**  
The notified body 4Ward Testing Ltd, identification number 2538 performed initial type tests under system 3 and issued report no. NLR1831.
  
10. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**  
Not Applicable.



**11. Declared Performance**

<b>EN 15651-1: F-INT-EXT: CLASS – 20HM</b> <b>Pre-Conditioning: Method A.</b> <b>Substrate: Mortar – without primer.</b>		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	Class F	
Release of Chemicals	See product safety data sheet	
Water Tightness & Air Tightness as determined by:		
Resistance to flow (ISO7390)	≤ 3mm	EN 15651-1: 2012
Loss of volume (ISO10563)	≤ 10%	EN 15651-1: 2012
Elastic recovery (ISO7389)	≥ 60%	EN 15651-1: 2012
Tensile properties at maintained extension after immersion in water (ISO10590).	NF	EN 15651-1: 2012
Secant tensile modulus at 23°C (ISO8339).	> 0.6 MPa.	EN 15651-1: 2012
Durability	Pass	EN 15651-1: 2012

**Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:**

Not relevant


**12. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for on behalf of Hodgson Sealants (Holdings) Ltd. by



Craig Wear  
Technical Services Consultant  
Beverley, 2<sup>nd</sup> April 2015



 2538
Hodgson Sealants (Holdings) Ltd, Belprin Road, Beverley, East Yorkshire, HU17 0LN, UK.  15  Reference No: DOP2015-1-HS30
<b>HS30</b> EN 15651-1: F-INT-EXT: CLASS – 20HM Pre-Conditioning: Method A. Substrate: Mortar – without primer.
EN 15651-1: F-INT-EXT: Sealant for façade for interior and exterior application. Reaction to Fire Class F Resistance to flow ≤3mm Loss of volume ≤10% Elastic recovery ≥60% Tensile properties at maintained extension after immersion in water NF Secant tensile modulus at 23°C >0.6 MPa Durability Pass